

Calcium Aluminate Cement. Edinburgh, Scotland, 2001.

13. Antonovic, V. A review of the possible applications of nanotechnology in refractory concrete [Text]. / V. Antonovic, I. Pundiene, R. Stonys, J. Cesniene, J. Keriene // Journal of civil engineering and management. 2010 – N. 16(4) – P. 595–602.

14. Fryda, H. Relation between setting properties of low cement castables and interactions within the binder system (CAC-Fillers-Additives-Water) [Text] / H. Fryda, K. Scrivener, Th. Bier, B. Espinosa // J. Amer. Ceram. Soc. 1997. – V. 3. – P. 1315–1323.

15. Пивинский, Ю. Е. О Влиянии разжижающих добавок на реотехнологические свойства ВКВС боксита [Текст] / Ю. Е. Пивинский, Ю. Н. Ермак, А. В. Череватова, Н. А. Шаповалов // Новые огнеупоры. – 2003. – №5. – С. 91–97.

16. Кашеев, И. Д. Влияние различных ПАВ на свойства алюмосиликатного бетона [Текст] / И. Д. Кашеев, К. Г. Земляной // Новые огнеупоры. – 2012. – № 7. – С. 29–31.

17. Хоммер, Х. Применение поликарбосилатных эфиров в качестве дефлокулянтов в огнеупорных бетонах [Текст] / Х. Хоммер, К. Вутц, Й. Зайерль // Огнеупоры и техническая керамика. – 2007. – № 12. – С. 43–47.

18. Кашеев, И. Д. Регуляторы реологических свойств неформованных огнеупоров [Текст] / И. Д. Кашеев, К. Г. Земляной // Новые огнеупоры – 2005. – №9. – С. 44–48.

19. Пивинский, Ю. Е. Диспергирующие (дефлокулирующие) глиноземы. [Текст] / Ю. Е. Пивинский, Пав. В. Дякин, П. В. Дякин // Новые огнеупоры. – 2004. – №3. – С. 29–38.

20. Myhre, B. Substitution of reactive alumina with microsilica in low cement and ultra low cement castables [Text] / B. Myhre, Aase M. Hundere // Part I: Properties Related to Installation and Demoulding. 1997. – N. 4 – 7. – P. 91–100.

21. Песчанская, В. В. Низкоцементный корундовый бетон с модифицированным матричным компонентом [Текст] / В. В. Песчанская, А. С. Макарова, Я. Н. Питак // Огнеупоры и техническая керамика. – 2013. – №3 – 4. – С. 16–21.

22. Report on Advanced civil engineering materials based on inorganic polymers [Электронный ресурс] / P. W. Brown, D. Shi, W. Ma, J. Bothe, E. Gruczcinski, J. Dumm, J. Gulick, R. Dudenhofer // Washington. – 1993. Режим доступа: URL: <http://www.dtic.mil/dtic/tr/fulltext/u2/a270837.pdf>.

23. Пісчанська, В. В. Вплив поверхнево-активних речовин на дефлокуляцію алюмінаткальцієвого цементу [Текст] / В. В. Песчанская, О. С. Наумов, І. В. Голуб, Г. С. Макарова, Я. М. Пітак // Вісник НТУ „ХПІ”. – 2011. – №48. – С. 72–77.

24. Кузнецова, Т. В. Глиноземистый цемент [Текст] / Т. В. Кузнецова, Й. Талабер. – М.: Стройиздат, 1988. – 272 с.

References

1. Primatchenko, V. V, Martynenko, V. V, Babkin, L. A, Soloshenko, L. N. (2003). Alyumosilicatnye nizkotsementnye bet ony dlya futerovock elementov metalurgicheskikh agregatov. Metalurgiya i gornorudnaya promyshlenost, 5, 64–66.

2. Egorov, I. V. (2006). Opyt ekspluatatsii neformovannykh ogneupornykh materialov i izdelii proizvodstva OOO „Keralit” v teplovykh agregatakh chernoy metallurgii. *Novye ogneupory*, 7, 12–18.
3. Migal, V. P., Margashvili, A. P., Skurikhin, V. V., Rusakov, G. V., Alekseev P. E. (2009). Neformovannyye ogneupornyye materialy dlya metallurgicheskoy promyshlennosti. *Ogneupory i tekhnicheskaya keramika*, 4 – 5, 27–33.
4. Migal, V. P., Skurikhin, V. V., Bulin, V. V. (2011). Neformovannyye ogneupory, vypuskaemye OAO «Borovchinskiy kombinat ogneuporov». *Novye ogneupory*, 10, 11–14.
5. Pivinskii, YU. E (2005). Neformovannyye ogneupory: spravoch. izd. v 2 t. M.: Teplotekhnika, 1: Obshchie voprosy tekhnologii, 448.
6. Mathieu, A. (1993). Aluminous cement with high alumina content and chemical binders. The engineering and use of monolithic refractories South Africa.
7. Parr, C., Revais, C., Valdelievre, B., Namba, A. (2000). The effect of ambient temperature upon the placing properties of deflocculated castables. Presented at TARJ Conference. Japan.
8. Parr, C., Assis, G., Fryda, H., Liyama, M., Borovsky, A (2010). The effect of environmental temperature conditions on the rheology of deflocculated refractory castable. Presented at Annual de Materias Primas, Montaje y Maquinaria de Refractorios.» organizado por ANFRE.
9. Nilforoushan, M. R., Talebiaan, N. (2007). The Hydration Products of a Refractory Calcium Aluminate Cement at Low Temperatures. *J. Chem. Chem. Eng.*, 26, 2, 71–76.
10. Payne, D. R., Sharp, J. H. (1989). The Nature of the gel phase in calcium aluminate cements, the microstructure and chemistry of cement and concrete. Presented at Aberdeen, Scotland.
11. Cuney, T. (1998). Chemical Preparation of the Binary Compounds in the CaO-Al₂O₃ System by Self Propagating Combustion Synthesis. *J. Amer. Ceram. Soc.*, 81, 9, 2853.
12. Scrivener, K. L. (2001). Historical and Present Day Application of Calcium Aluminate Cements. In Proc. of the 11th International Conference on Calcium Aluminate Cement. Edinburgh, Scotland.
13. Antonovic, V., Pundiene, I., Stonys, R., Cesniene, J., Keriene, J. (2010). A review of the possible applications of nanotechnology in refractory concrete. *Journal of civil engineering and management*, 16(4), 595–602.
14. Fryda, H., Scrivener, K., Bier, Th., Espinosa, B. (1997). Relation between setting properties of low cement castables and interactions within the binder system (CAC-Fillers-Additives-Water). *J. Amer. Ceram. Soc.*, 3, 1315–1323.
15. Pivinskii, YU. E, Ermak, E. N., Cherevatova, A. V., Shapovalov, N. A. (2003). O vliyaniy razzhizhayushchikh dobavok na reotekhnologicheskie svoystva VKVS boksita. *Novye ogneupory*, 5, 91–97.
16. Kashcheev, I. D, Zemlyanoy, K. G (2012). Vliyaniye razlichnykh PAV na svoystva alyumosilikatnogo betona. *Novye ogneupory*, 7, 29–31.

17. Hommer, H., Vutts, K., Zayerl, J. (2007). Primenenie polikarboksilatnykh efirov v kachestve deflokulyantov v ogneupornykh betonakh. *Ogneupory i tekhnicheskaya keramika*, 12, 43–47.

18. Kashcheev, I. D., Zemlyanoy, K. G. (2005). Regulyatory reologicheskikh svoystv neformovannykh ogneuporov. *Novye ogneupory*, 9, 44–48.

19. Pyvynskyy, YU. E., Dyakyn, Pav. V., Dyakyn, P. V. (2004). Dispergiruyushchie (deflokuliruyushchie) glinozemy. *Novye ogneupory*, 3, 29 – 38.

20. Myhre, B., Hundere, Aase M. (1997). Substitution of reactive alumina with microsilica in low cement and ultra low cement castables. Part I: Properties Related to Installation and Demoulding, 4 – 7, 91–100.

21. Peschanskaya, V. V., Makarova, A. S., Pitak, Ya. N. (2013). Nizkotsementny korundovy beton s modifitsirovannym matrichnym komponentom. *Ogneupory i tekhnicheskaya keramika*, 3 – 4, 16–21.

22. Brown, P. W., Shi, D., Ma, W., Bothe, J., Gruczcinski, E., Dumm, J., Gulick, J., Dudenhofer, R. (1993). Report on Advanced civil engineering materials based on inorganic polymers. Washington. Available at: <http://www.dtic.mil/dtic/tr/fulltext/u2/a270837.pdf>.

23. Pischanska, V. V., Naumov, O. S., Golub, I. V., Makarova, G. S., Pitak, Ya. M. (2011). Vplyv poverkhnevo-aktyvnykh rehovyn na defloculyatsiyu alyuminatkaltsievogo tsementa. *Vistnyk NTU «KhPI»*, 48, 72–77.

24. Kuznetsova, T. V., Talaber, Y. (1988). *Glinizemisty tsement*. M.: Stroyizdat, 272.

A tendency to increasing the volumes of production and application of low cement refractory concrete has determined the development of theoretical and practical aspects of modifying concrete with surfactants. Varying the rate of hydration of calcium aluminate cement, surfactants (deflocculants) has influenced the rheotechnological characteristics of concrete masses and their consolidation, formation of the solid low porosity concrete structure, both when hardening at normal temperatures and in conditions of thermal heating.

The influence of the low cement refractory cement deflocculant – sodium tripolyphosphate and a complex modifier, containing sodium tripolyphosphate, and an organic superplasticizer, on changing the nature of hydration processes of cement and the ratio between the crystalline and amorphous phases, the strength properties of cement stone at early stages of hardening, was studied in the paper. The differences in spatial orientation and density of the nanostructures on the surface of cement crystallohydrates, modified with sodium tripolyphosphate and the complex modifier were revealed. It was found that the complex modifier, presented by surfactants of different nature, has a significant influence on the formation of a finely porous and mechanically strong structure of composite material, physical and technical properties of the heat-treated concrete.

Keywords: low cement refractory concrete, calcium aluminate cement, hydration, modifier, amorphous phase, crystallohydrates, microstructure.